18400

ENGINEERING-SCIENCE, INC.

1700 Broadway, Suite 900 Denver, Colorado 80290 phone: (303) 831-8100 • telecopy (303) 831-8208



000022686

MEETING NOTES

TO:

Distribution

DATE:

December 15, 1993

FROM:

Philip Nixon

MEMO #:

SP307:121593:01

PROJECT #:

Solar Pond IM/IRA

ATTENDANCE:

Harlan Ainscough, CDH

Mark Austin, EG&G

Phil Nixon, ES

Richard Henry, ES

Andy Ledford, EG&G Alan MacGregor, ERM

John Haasbeek, ERM

Frazer Lockhart, DOE/SMS

Dave Ericson, EG&G Steve Howard, ERM

Rick Wilkinson, ES

Dave Myers, ES Peg Witherill, DOE

Arturo Duran, EPA

DISTRIBUTION:

Attendees

L. Benson

A. Conklin

P. Breen

H. Heidkamp

K. Cutter

S. Stenseng

A. Fricke

R. Stegen

T. Kuykendall

T. Evans

B. Cropper

C. Montes

B. Wallace, EG&G (Admin.

Record) (2)

K. Ruger, EG&G

K. London, EG&G

Martin McBride

Helen Belencan, DOE

Steve Cook

Joe Schieffelin, CDH

Steve Paris, EG&G

Ted Kearns, DOE/KMI

Bob Segris, LATO

Randy Ogg, EG&G

Steve Keith, EG&G

MAR 1994 RECORDS CENTER IS

SUBJECT:

Weekly Status Meeting

DOCUMENT CLASSIFICATION AREVIEW WAIVER PER CLASSIFICATION OFFICE 1

R9-10-17.WPF

ADMIN RECORD

A-0U04-000656

1.) Introductions

Andy Ledford introduced Dave Ericson as the EG&G design and construction manager for the OU4 IM/IRA. He also introduced Erika Atchison as the OU4 Program Administrator.

The purpose of the meeting was to determine a path forward for the conceptual design of a selected remedial/closure alternative. The discussions focused on the different media (contaminated media, liners, and hotspots). It was noted that regulatory approval was not expected at this time, but an agreement on a path forward was needed that would be approved if DOE demonstrated that it would be implemented in a manner which would be protective of human health and the environment.

2.) Contaminated Media

Contaminated media is defined as soils outside the area under the proposed engineered cover that have concentrations which exceed the Preliminary Remediation Goals (PRGs). Hot spots are defined as materials under the area of the proposed engineered cover that have concentrations exceeding the PRGs and present an unacceptable risk to human health and the environment as demonstrated through vadose zone transport modeling to groundwater.

Phil Nixon presented the areal extent of the contaminated media on the north hillside and presented an estimated volume of material that exceed the PRGs and Land Disposal Restriction concentrations.

It was agreed that soils exceeding PRGs could be consolidated under the engineered cover without enacting a Corrective Actions Management Unit (CAMU) concept. However, soils exceeding their LDR levels could not be consolidated under the engineered cover. There is approximately 3,000 cubic yards of soil that exceed the LDR concentrations. It was discussed that additional testing of archived RFI/RI samples for TCLP concentrations might demonstrate compliance with the LDR concentrations. The RFI/RI results are based on a total metals analysis. A reduction in the OU4 concentration would be dependent upon the actual dilution factor being greater than the regulatory default value of 20. EG&G will pursue TCLP analysis or sensitivity analysis to determine if the north hillside soil concentrations are less than the LDR concentrations.

Harlan Ainscough indicated that the Colorado Hazardous Waste Control Commission is considering adopting the CAMU rule. He specified that its acceptance was likely and recommended that DOE prepare the IM/IRA assuming that it would be adopted.

It was agreed that DOE would prepare the IM/IRA specifying that radiologically-contaminated hillside soils and soils that do not have an LDR concern may be consolidated under the covered area. It is likely that contaminated soils from the berms to the seep areas will be consolidated, but that soils north of the seep areas that are impacted by groundwater will be addressed by the Phase II program. It will be assumed

R9-10-17.WPF 2

that the CAMU concept will be adopted by CDH. DOE will develop a contingency plan if the CAMU concept is not adopted. The contingency plan may consist of:

- 1) additional TCLP analysis to demonstrate compliance with LDR concentrations
- 2) excavate and dispose of soils exceeding LDR concentrations
- 3) extend the engineered cover over the areas where LDR concentrations are exceeded.

The IM/IRA document will have to justify the use of the CAMU concept.

3) Liners

Frazer Lockhart agreed that DOE would excavate portions of the liners and subgrade if it was determined that this was necessary to be protective of human health and the environment. Leaving the liners in-place would provide a protective barrier against liquids migrating to the subgrade materials and would provide a stable base for construction of an engineered cover. Harlan Ainscough specified that the liners could remain in place if DOE could demonstrate that the impacts to groundwater from horizontal and vertical migration were insignificant and protective of human health and the environment for 1000 years. Harlan indicated that CDH believes the geology/hydrogeology of the site are not adequate to meet the 1000 years siting criteria. However, engineering remedies/ upgrades may be acceptable for preventing adverse impacts for the 1000 year period. The siting requirements will be identified as location-specific ARARs.

It was agreed that the liners could remain in place if it could be demonstrated that the entire remedial alternative would be protective of human health and the environment and prevent groundwater contact with the liners and contaminated media for 1000 years. Protection of groundwater must consider both vertical and lateral migration. It was agreed that this does <u>not</u> mean that the engineered barrier must be designed for a passive life span of 1000 years.

DOE will provide vadose zone modeling results to demonstrate the protection of human health and the environment. Performance modeling will also be used to determine the requirements of the engineered barrier.

Harlan specified that the engineered cover would only have to be designed for a 30-year life span if the liners were removed. Frazer Lockhart indicated that DOE might have a difficult time selling a 30-year design to the public.

It was agreed that an engineered cover could be selected as the OU4 IM/IRA if the above-mentioned requirements were adequately addressed.

Arturo Duran stated that it would be possible to remove and consolidate the liners within one of the Solar Evaporation Ponds. It was agreed that this was an option that could be considered.

3

R9-10-17.WPF

Alan MacGregor discussed the potential to phase the construction of the engineered barrier such that it could be assessed after the post-closure period whether a 1000 year life span was required. Phil Nixon presented a flow diagram that could be followed to implement this approach. It was agreed that this option could also be considered.

4.) Performance Objectives

Phil Nixon provided the team with a trip report from the meetings in Hanford and discussed the applicability of the Hanford design criteria to the OU4 site. It was agreed that the engineered cover should:

- 1.) should be designed to function in a semi-arid region
- 2.) should be designed to minimize infiltration
- 3.) should function with minimal maintenance
- 4.) should minimize animal intrusion
- 5.) should minimize erosion
- 6.) should comply with RCRA/CERCLA requirements

It was agreed that the engineered cover design should not address the prevention of human intruders. The prevention of human intruders should be addressed in the future by a sitewide Record of Decision.

Frazer Lockhart specified that the design assumptions made at Hanford should be assessed for their applicability at Rocky Flats. The environmental conditions and levels of contaminants are different between the two sites. For example, the radiological soil concentrations at Hanford are 4-5 orders of magnitude higher than the concentrations in Rocky Flats soils.

5.) Phase II RFI/RI Status

Richard Henry requested if an additional 2 weeks could be added to the schedule for the Phase II RFI/RI workplan once the task was held up in procurement. Andy Ledford said that he would prefer to submit the workplan at the same time as the round table IM/IRA draft. Frazer Lockhart indicated that it might be possible since an IAG date would not be missed.

6.) Phase I RFI/RI Drilling in Ponds 207C and 207B-South

It was discussed that drilling in Pond 207B was scheduled at the end of December, and drilling in Pond 207C was scheduled ate the end of March. It was agreed that both the ponds could be drilled at the end of March to save the cost of multiple mobilization and demobilization costs.

7.) **Building 788**

There is uncertainty whether the removal of Building 788 is in or out of the OU4 IM/IRA. DOE wishes to remove the building for re-use as soon as possible to meet waste

management needs elsewhere on site, and utilize funding available in FY94. If Building 788 is put back into the OU4 IM/IRA, then there should be no impact to the current IM/IRA schedule because there is a current contract for the building removal. The document should be ready for submittal with the IM/IRA.

8.) Conclusion

The following agreements were listed on the chalkboard during the meeting to guide the Alternative II design.

- 1.) Consolidate Pu/Am/U and constituents less than LDRs into the Ponds.
- 2.) TCLP for Ni/Cd to calculate LDRs.
- 3.) Provide protection of constituents exceeding LDRs
 - consolidate contaminants exceeding LDRs
 - hot spot removal/treatment/disposal
 - extend engineered cover
- 4.) Liners may remain provided that groundwater is protected
 - lateral flow presence
 - contaminant transport less than LDR/PRG
- 5.) Overall solution protective for 1000 years.

Philip Nixon, Project Manager

AHAChment | SP307:121593:01 Page 10f2

OPERABLE UNIT 4/SOLAR EVAPORATION PONDS

DECEMBER 21, 1993

AGENDA

SCHEDULE STATUS/PROGRESS-J. A. LEDFORD
ROUNDTABLE REVIEW SCHEDULE

8:00-8:30

POST CLOSURE MONITORING AND MAINTENANCE

8:30-10:30

REGULATORY FRAMEWORK-R. OGG

VADOSE/UNSATURATED ZONE MONITORING TECHNIQUES/PRINCIPALS-L. G. EVERETT

POST CLOSURE PERFORMANCE
MONITORING-L. G. EVERETT/S. CULLEN

POST CLOSURE PERFORMANCE MONITORING INSTRUMENTATION-S. CULLEN

OU 4 PHASE I RFI/RI VADOSE ZONE ANALYSIS-R. HENRY

10:30-11:00

PHASE II RFI/RI WORK PLAN-R. OGG

11:00-11:30

WORK PLAN OBJECTIVES

WORK PLAN CONTENTS

INTRODUCTION (5 PGS.)
ENVIRONMENTAL SETTING (10 PGS.)
DATA EVALUATION/SUMMARY (10-15 PGS.)
DATA OBJECTIVES/REQUIREMENTS (5-10 PGS.)
FIELD SAMPLING PLAN (15-20 PGS.)
PHASE II RFI/RI TASKS/SCHEDULE (5-10 PGS.)
HUMAN HEALTH RISK ASSESSMENT WORK PLAN

(STANDARD)

ENVIRONMENTAL EVALUATION WORK PLAN (STANDARD)*

Attachment 1 5P 307:121593:01 page 2012

QUALITY ASSURANCE PROJECT PLAN (STANDARD) STANDARD OPERATING PROCEDURES-IF REQUIRED REFERENCES APPENDICES

* THE ENVIRONMENTAL EVALUATION FIELD SAMPLING PLAN FOR OU 4 HAS BEEN COMPLETED IN PHASE I RFI/RI AND THE DATA COLLECTED HAS BEEN ARCHIVED. THEREFORE, A EEWP WILL NOT BE DEVELOPED FOR THE PHASE II RFI/RI WP.

LUNCH

11:30-12:30

CONTENTS OF THE CONCEPTUAL DESIGN REPORT-ES

12:30-2:00

Table xx. Contaminants of Concern for OU4 IM/IRA Mote: All Calculations are Based on OU4 Data From 1987 - September 30, 1993 Only

				,			,			·	. — —		
los ec	P*A.#300	Nas		(80%) PT 1	1 3 7804)		956	9.27		006'11	11,900	Arochior – 1254 (ug/kg)	
			i						<u> </u>		}	<u> श्रुक्तांवकः</u>	
lio2 aco	heV ≈ 2000	SON SO SOME		 		Possible Hot Spots	096'\$	096'\$		24,000	88.088	Bia(2-ethyldexyl)phthalate (ug/kg)	
			:									epinegnO alneloV - im>2	
ins soil	98A-401-000	k bM	000000000000000000000000000000000000000	l Negation in	Kanany	Possible Hot Spots	2.66	5.62	£-1Z	180	13.4	Nickel (mg/kg)	
PRG - Possible Hot Spots	8	8	88.1	10.8•	034	PRG	9010	9010	900	8.1	010	Mercury (mg/kg)	
[jog esc	OOC (or Vad	you				Possible Hot Spots	8.62	8.62	12.4	48.4	\$102	Chromium (VI) (mg/kg)	
Possible Hot Spots – Dats source pre-Phase Phase I RFI/RI(*) PRG – Possible Hot Spots	120	120	85	11,600*	183	DA1	Д₹	CC for Surficial Soil	6610	086	6'67	Barium (mg/kg) Osdmium (mg/kg)	
				100,		99999951177991999131					11260-12-3	इंग्युं र	
												ध्यञ्चलाच्याच्या	
2013年 2017年 201	PrA 201 2000	s to Mars		e Corre	,, w	PRG	είιο	בנוס		006,11	006'11	Arochlor – 1254 (ug/kg)	
	,				:					i 		<u> १ क्लंक्</u>	
PRG - Data source pre-Phase 1 RFI/RL(*)	1 ***	7399		+009'1	+009'ī		- 888	OC tor Surfail Sail	NosC	!		Pentachlorophenol (ug/kg)*	
PRG – Data source pre – Phase I RF/RM(°) PRG – Data source pre – Phase I RF/RM(°)		702		330•	330•		198	lies lieding not DO:				N - nitrosodiphenylamine (ug/kg)* N - nitrosodipropylamine (ug/kg)*	
PRG - Data source pre-Phase I RFI/RI(°)		00/56 \$17		•000°1	330° 1,600°		2.000	OC for Surficel Soil SOC for Surficel Soil				Indeno(1,2,3-od)pyrene (ug/kg)*	
PRG - Data source pre-Phase I RFI/RI(*)	eei	13.3		330•	330•			OC for Surficel Soil				Hexadalorobenzene (ug/kg)*	
Pozzible Hot Spots - Data sour oz pre-Phase Phase I RFI/RI(*)	COC TO APP					PRG	2.72	s.rs		0\$6	212.83	Chyrene (ug/kg) Bia(2-ethyldery)phida bic (ug/kg)	
PRG - Data source pre - Phase I RH/RI(°)		26Z		*000*	330•	98G 98G	102	105		1,500	11.12£ 55.035	Benzo(k)fluoranthe ne (ug/kg) Bio(2-ethylpezy)mhtha hie (ug/kg)	
PRG - Data source pre-Phase I RFI/RI(*)		7.62		330•	330•	PRG	668.0	0.833		004,1	19.COC	Benzo(b)Buorant bene (ug/kg)	
PRG - Data source pre-Phase I RFI/RI(*)		643		330•	330+	PRG	เรเก	0.163		006	21278	Benzo(a)pyrene (ug/kg)	
PRG — Data source pre—Phase I RF/RI(°) PRG — Data source pre—Phase I RF/RI(°)		910Z 06Z		330•	330•	984	ן עצט	SOC for Surficed Soil 772.0		048	TT.781	Denzo(a)anthra cene (ug/kg)	
	PRA 201 2000			-055	-022	PRG	1 411	1-51-94-52-750		00+	00>	1,4-dichlorobenzene (ug/kg)	
***				.								Seinst O MinhoV - im 52	
ьке	785.0	. 782.0	ωτο	L810	zσ	Background	94.1	4,450.0	92.1	cco	σរន	(g\Dq) \cdot \cdot - muins\(U \)	
. Sag		721	001	57	3.25	PRG	76>0	7697	סוז	£1	10.6	Plutonium - 239/240 (pCJ/g)	
, эяч	907	706	σοι	19	88.0	Background	96610	034	96610	110	10.8	Americium-241 (pQ/g)	
·						•						<u>Radionudides</u>	
Mox & COC for Vadose Soil						Background	1.05	0.0148	1.05	9.6) 'I	Beryllium (mg/kg)	
												<u> अल्बा</u> र	
								<u> </u>				क्रक्कां क्रा	
(9)	(3)	<i>ω</i>	(5)	(2)	(1)	(9)	(3)	(****************	(E) (mustiment)	(7)	(1)	#177700 IO	
Selection Criteria	TagasT [sva.]	PRG (Construction Workst)	(borgabe)	(All Data)	U #829 bUO (grad llA)	Selection Criteria	13gtsT [sva.]	PRG (fursbissR stutuf)	(Beckgrod)	Max Value (specifical)	U 44CQ \$UO	Contaminant an example	
	- 'E) Lio2 3001			1-71-371	- 2030 7110			(£ - 0) (105 (vp)	ums			1	
							STON						

^{1.} Cabrained 9.7% upper comeldener limit on the artifamenic mean uning bodh pre-Phan I RPVRI and Phar IRPVRI den except as discussed in next note that when the data country of the contract o

the 95% upper tolerand limit OR the reported maximum whole one used as the 95% UCL value. A Reported maximum value using both pre -Pham I RPI/RI data except as discussed in text

to the seal man de artification de action and a seal of a sea seal of a

^{4.} Cabralund rink - based preliminary remediation goal for the fatters readent exposure scenario (compasson crimeria).

Targest concentration used to define analyse as constantings of concentral

^{6.} Details on selection criteria (s.g., inrget level source, but spot potential).

Celevatused rink - bessed preliminary remediation goal for the construction worker exposure scenario (comparison criteria)

Table x.x (continued, page 2). Contaminants of Concern for OU4 IM/IRA Note: Remaining analytes have been classified as COCs in the absence of toxicity data to be used to calculate preliminary remediation goals; all data based on OU4 data from 1987 — September 30, 1993.

NOTE: * = analyte/max, value only measured above reported detection limit during pre-Phase I RFI/RI sampling programs, Vadose Soil (3" - 12') Surficial Soils (0 - 3") Contaminant Freq of Range of OU4 Range of OU4 Freq of Range of OU4 Range of OU4 Detected Conc. of Concern Detects Detect Limits Selection Criteria Detects **Detect Limits** Detected Conc. Selection (10) an (8) (9) (9) (10) (11)Radionuclides · Tritium (pCi/ml) 14/39 0 - 4.10.04 - 1.3No toxicity data 133/170 0 - 0.590.11 - 62. No toxicity data Organics 1,1,1 - trichloroethane (ug/kg) Not a COC for Surficial Soil 20/171 0 - 56 - 29No toxicity data Not a COC for Surficial Soil 2-hexanone (ug/kg) 21/161 0 - 1011 - 58No toxicity data 11/171 470 - 1,200Phenanthrene (ug/kg) 370 - 600No toxicity data 8/35 330° 0 No toxicity data -Data source pre-Phase I RFI/RI(*) 1,2-dichloropropane (ug/kg) Not a COC for Surfical Soil 20/171 6 - 290 - 5No toxicity data 1,4-dichlorobenzene (ug/kg) 400 No toxicity data 1/4 8/35 0 330° No toxicity data -Data source pre-Phase I RFI/RI(*) Not a COC for Surfical Soil Chloroethane (ug/kg) 21/167 0 - 1011 - 58No toxicity data

^{8.} Frequency of detection indicates the frequency with which the analyte was measured above the reported detection limit.

^{9.} Range of reported chemical-specific detection limits in data for OU4.

^{10.} Range of measured concentrations exceeding the reported, corresponding detection limit.

^{11.} Details on selection criteria (i.e., lack of toxicity data).

Attachment 3 SP3UT: 121593:01 page 1 of 2

CONCEPTUAL DESIGN DOCUMENTATION OUTLINE OU4 IM/IRA

PART IV RECOMMENDED IM/IRA ALTERNATIVE

IV.1 Description and Rationale for Selection

- IV.1.1 Selection of a Closure/Remediation alternative
- IV.1.2 Description of the Selected Alternative

IV.2 Design Basis

- IV.2.1 Functional Objectives
- IV.2.2 Design Requirements
 IV.2.3 Applicable Codes and Standards
- IV.2.4 Constraints and Limitations
- IV.2.5 Assumptions

IV.3 Conceptual Design

- IV.3.1 Engineered Cover and Site Layout
 - detailed design description and justification
 - HELP model (description, inputs, outputs)
 - drawings
- IV.3.2 Utilities
 - detailed design description and justification
 - drawings

IV. 4 Outline Specifications

- IV.4.1 Engineered Cover and Site Layout
- IV.4.2 Utilities

IV.5 Implementation Plan and Proposed Schedule

- IV.5.1 Engineering Implementation Studies
 - geotechnical testing workplan
 - utility location verification workplan
- IV.5.2 Schedule

IV.6 Cost Estimate

- IV.6.1 Cost and Funding Plan
- IV.6.2 Procurement Plan

IV.7 Construction Quality Assurance Plan

IV.8 Waste Management Plan

IV.9 Power Modification Request and Power Usage Survey

IV.10 IM/IRA Risk Analysis and Potential Impact Determination

- IV.10.1 Human Health Risks
- IV.10.2 Ecological Risks
- IV.10.3 Impact to Air Quality
 - air modeling (description, input, output)
- IV.10.4 Impact to Water Quality
 - groundwater (V-Leach, description, input, output)
 - surface water

- IV.10.5 Impact from the Commitment of Irreversible and Irretrievable Resources
- IV.10.6 Transportation Impacts
- IV.10.7 Short Term vs. Long Term Impacts
- IV.10.8 Impact to Cultural/Historical and Archeological Resources
- IV.10.9 Cumulative Impacts
- IV.11 Comparative Analysis Between the No-action and Preferred Alternative
- IV.12 Consistency with Final Remedies
- IV.13 Compliance with ARARs and Permit Information Summary
- IV.14 Health and Safety Considerations